

## LA-UR-17-30580

Approved for public release; distribution is unlimited.

Title: Building a Predictive Capability for Decision-Making that Supports  
MultiPEM

Author(s): Carmichael, Joshua Daniel  
Nemzek, Robert James

Intended for: Report

Issued: 2017-12-05 (rev.1)


---

**Disclaimer:**

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

# Building a Predictive Capability for Decision-Making that Supports MultiPEM

*Application to Seismic, Acoustic and Radio Emissions that Signal Near Surface Explosions*



**Joshua D. Carmichael**  
**Robert J. Nemzek**

13-Nov-2017

# ***Multi-Phenomenological Explosion Monitoring (MultiPEM)***

***What is the Objective of MultiPEM?***

# *Multi-Phenomenological Explosion Monitoring (MultiPEM)*

## *What is the Objective of MultiPEM?*

- *Multi-phenomenological explosion monitoring (multiPEM) is a developing science that uses multiple geophysical signatures of explosions to better identify and characterize their sources.*
- *MultiPEM researchers seek to integrate explosion signatures together to provide stronger detection, parameter estimation, or screening capabilities between different sources or processes.*
- ***This talk** will address forming a **predictive capability** for screening waveform explosion signatures to support multiPEM*

# *Multi-Phenomenological Explosion Monitoring (MultiPEM)*

## *What is the Objective of MultiPEM?*

- A ***predictive capability*** means that if a hypothetical explosion of an anticipated size/yield occurs, we can quantify how well we can detect, associate, screen, locate, or characterize the signatures or parameters of that source with uncertain data


# Focus: Waveform Signature Detection

## Example Explosion Signatures

Aboveground explosion signatures include **radio**, **acoustic**, and **seismic** waveforms. These waveforms give data on source size and emplacement

## What is our Predictive Capability?

A hypothetical explosion of a given size occurs. How well we can **detect** signatures of that source with uncertain data?



# Monitoring Detection Problems that Require a Predictive Capability

## This Talk Answers Three Research Challenges

1. Does **mean** predicted detector performance match **mean** observed performance?
2. Does observed versus predicted detector performance exceed day-to-day observed variability? That is, does predicted performance assembled on day **A** match observations from day **A** better than observations assembled on day **B**?
3. What is the range in observed versus predicted magnitude discrepancies? That is, if a detector predictively identifies explosions of magnitude  **$m$**  with probability  **$\text{Pr}_D$** , what is the observed, absolute range  **$\Delta m$**  the detector identifies explosions for that  **$\text{Pr}_D$** ?



# ***Decision Theory Statement for Any Signature***


***Binary Testing on Two Source Types***

# Building a Detector (1/2)

- A waveform detector is a decision rule that compares a statistic  $s_k(\mathbf{x})$  with a threshold  $\eta$  to test if data  $\mathbf{x}_k$  that records signature  $k$  is evidence for a target signal (hypothesis  $\mathcal{H}_1$ ) or not (hypothesis  $\mathcal{H}_0$ ):

$$\underset{\mathcal{H}_0}{s_k(\mathbf{x})} \underset{\mathcal{H}_1}{\geq} \underset{\mathcal{H}_0}{\eta}$$

- The statistic  $s_k(\mathbf{x})$  has PDFs that depend on the presence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$ ) or absence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_0)$ ) of that target signal
- The probability  $\Pr_D$  of correctly deciding a target signal is present compared with the false-alarm probability  $\Pr_{FA}$  quantifies the detector's performance




# Building a Detector (2/2)

- A waveform detector is a decision rule that compares a statistic  $s_k(\mathbf{x})$  with a threshold  $\eta$  to test if data  $\mathbf{x}_k$  that records signature  $k$  is evidence for a target signal (hypothesis  $\mathcal{H}_1$ ) or not (hypothesis  $\mathcal{H}_0$ ):

$$s_k(\mathbf{x}) \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} \eta$$

**Examples:** *STA/LTA, correlation, subspace, SNR, spectrogram, cone*

- The statistic  $s_k(\mathbf{x})$  has PDFs that depend on the presence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$ ) or absence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_0)$ ) of that target signal
- The probability  $\Pr_D$  of correctly deciding a target signal is present compared with the false-alarm probability  $\Pr_{FA}$  quantifies the detector's performance




# Building a Detector's Predictive Capability (1/2)

- A waveform detector is a decision rule that compares a statistic  $s_k(\mathbf{x})$  with a threshold  $\eta$  to test if data  $\mathbf{x}_k$  that records signature  $k$  is evidence for a target signal (hypothesis  $\mathcal{H}_1$ ) or not (hypothesis  $\mathcal{H}_0$ ):

$$\underset{\mathcal{H}_0}{s_k(\mathbf{x})} \underset{\mathcal{H}_1}{\geq} \underset{\mathcal{H}_0}{\eta}$$

- The statistic  $s_k(\mathbf{x})$  has PDFs that depend on the presence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$ ) or absence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_0)$ ) of that target signal
- The probability  $\Pr_D$  of correctly deciding a target signal is present compared with the false-alarm probability  $\Pr_{FA}$  quantifies the detector's performance



## Problem Statement

**Challenge:** If a hypothetical event produces signature  $k$  and statistic  $s_k(\mathbf{x})$ , can we predict the probability  $\Pr_D$  of detecting that event?


Equivalently, what is the predictive capability of that detector?

# Building a Detector's Predictive Capability (2/2)

- A waveform detector is a decision rule that compares a statistic  $s_k(\mathbf{x})$  with a threshold  $\eta$  to test if data  $\mathbf{x}_k$  that records signature  $k$  is evidence for a target signal (hypothesis  $\mathcal{H}_1$ ) or not (hypothesis  $\mathcal{H}_0$ ):

$$\underset{\mathcal{H}_0}{s_k(\mathbf{x})} \underset{\mathcal{H}_1}{\geq} \underset{\mathcal{H}_0}{\eta}$$

- The statistic  $s_k(\mathbf{x})$  has PDFs that depend on the presence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$ ) or absence ( $f_S(s_k(\mathbf{x}); \mathcal{H}_0)$ ) of that target signal
- The probability  $\Pr_D$  of correctly deciding a target signal is present compared with the false-alarm probability  $\Pr_{FA}$  quantifies the detector's performance



## Problem Statement


**Method:** PDF  $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$  is effectively parameterized by the magnitude  $m$  of the hypothetical event that produces statistic  $s_k(\mathbf{x})$ .

We will compare observed detector counts with predicted counts

# ***Predicting the Capability of a Radio Emission, SNR Detector***


***Binary Testing on Two Source Types***

# Minie Data Collection: 70 Charge Shots



# Radio Emissions from Explosions (1/6)


**Hypothesis Test:** Source 0: No Explosion. Source 1: An Explosion






# Radio Emissions from Explosions (2/6)

**Hypothesis Test:** Source 0: No Explosion. Source 1: An Explosion




# Radio Emissions from Explosions (3/6)

**Hypothesis Test:** Source 0: No Explosion. Source 1: An Explosion




# Radio Emissions from Explosions (4/6)

**Hypothesis Test: Source 0: No Explosion. Source 1: An Explosion**




# Radio Emissions from Explosions (5/6)

**Hypothesis Test:** Source 0: No Explosion. Source 1: An Explosion



# Radio Emissions from Explosions (6/6)

**Hypothesis Test: Source 0: No Explosion. Source 1: An Explosion**



# Observed versus Predicted “ROC Curves”

## Observed ROC Curves

- Scale **template waveform** of amplitude  $A_0$  recording **template source** with magnitude  $m_0$  to amplitude  $A$  consistent with a signal triggered by source of magnitude  $m = m_0 + \Delta m$

$$A = 10^{\Delta m} A_0$$

- Repeatedly infuse scaled waveform into real, recorded noise sampled from multiple times and days
- Process noisy waveforms with radio emission, SNR detector over days and  $\Delta m$ . Dynamically adjust detector threshold  $\eta$  to maintain constant  $10^{-8}$  false alarm rate

## Predicted ROC Curves

- Estimate **parameters** that shape “explosion signal present” PDF during detector processing
- Construct temporally variable PDF curves and compute detection probabilities at each  $\Delta m$  value
- Integrate area right of concurrent detection threshold  $\eta$  to estimate detection probability  $\text{Pr}_D$ .
- Scale probability by the true number of infused waveforms to estimate expected number of counts  $N \cdot \text{Pr}_D$ .

# Detector Parameters of $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$ (1/2)

*Parameter that separates  $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$  and  $f_S(s_k(\mathbf{x}); \mathcal{H}_0)$  curves*

## Noncentrality Parameters

## Competing PDFs

### Radio, SNR Detector


- $\lambda = 10^{2\Delta m} \frac{A_0^2 N}{\sigma^2}$
- $\hat{\lambda} = \hat{N}_E \cdot 10^{\frac{e}{10}}$

### Acoustic Power Detector

- $\lambda = \text{SNR} \left( \frac{N_2}{N_1} \right) (N_2 - 2) - N_1$
- $\hat{\lambda} = Z \cdot \left( \frac{\hat{N}_1}{\hat{N}_2} \right) (\hat{N}_2 - 2) - \hat{N}_1$

### Seismic Correlation Detector

- $\lambda = (N - 1) \left( \frac{\rho^2}{1 - \rho^2} \right)$
- $\hat{\lambda} = (N - 1) \left( \frac{\hat{\rho}^2}{1 - \hat{\rho}^2} \right)$



# Detector Parameters of $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$ (2/2)

*Parameter that separates  $f_S(s_k(\mathbf{x}); \mathcal{H}_1)$  and  $f_S(s_k(\mathbf{x}); \mathcal{H}_0)$  curves*

## Noncentrality Parameters

### Radio, SNR Detector

- $\lambda = 10^{2\Delta m} \frac{A_0^2 N}{\sigma^2}$
- $\hat{\lambda} = \hat{N}_E \cdot 10^{\frac{e}{10}}$

### Acoustic Power Detector

- $\lambda = \text{SNR} \left( \frac{N_2}{N_1} \right) (N_2 - 2) - N_1$
- $\hat{\lambda} = Z \cdot \left( \frac{\hat{N}_1}{\hat{N}_2} \right) (\hat{N}_2 - 2) - \hat{N}_1$

### Seismic Correlation Detector

- $\lambda = (N - 1) \left( \frac{\rho^2}{1 - \rho^2} \right)$
- $\hat{\lambda} = (N - 1) \left( \frac{\hat{\rho}^2}{1 - \hat{\rho}^2} \right)$

## Parameter Dependencies

$N$  samples in window, noise variance  $\sigma^2$ , waveform amplitude  $A_0^2$ , source magnitude  $\Delta m$ ,  $e$  is the SNR (dB) statistic at detection, hats  $\hat{\cdot}$  are estimates of their arguments


$N_1$  samples in STA window,  $N_2$  samples in LTA window,  $\text{SNR}$  is the waveform signal to noise ratio,  $Z$  is the STA/LTA statistic at a detection, hats  $\hat{\cdot}$  are estimates of their arguments

$N$  samples in the,  $\rho$  is the cross-correlation coefficient and hats  $\hat{\cdot}$  are estimates of their arguments



# Operation of the Radio Emission, SNR Detector

## *Detect Scaled Waveforms Infused into Real, Recorded Radio Noise*



# *Quantifying the Predictive Capability of a Radio Emission, SNR Detector*

*Estimate Magnitude Differences between  
Predicted and Observed ROC Curves*

*Process over 12 Days,  $-2.3 \leq \Delta m \leq 0$*

# ROC Curve Comparison

## Three Research Challenges


1. Does **mean** predicted detector performance match **mean** observed performance?
2. Does observed versus predicted detector performance exceed day-to-day observed variability? That is, does predicted performance assembled on day **A** match observations from day **A** better than observations assembled on day **B**?
3. What is the range in observed versus predicted magnitude discrepancies? That is, if a detector predictively identifies explosions of magnitude **m** with probability  $\text{Pr}_D$ , what is the observed, absolute range  $\Delta m$  the detector identifies explosions for probability  $\text{Pr}_D$ ?

## Solution Method

1. Compute predicted and observed ROC curves over a magnitude grid, then average both of over time, and compare
2. Compare predicted ROC curves for each day to observed ROC curves for all days; then compare observed ROC curves against observed ROC curves on other days
3. Introduce ROC “magnitude discrepancy”: (i) select a probability interval; (ii) find probability  $\text{Pr}_D^{\max}$  in that interval with the max magnitude range across mean observed versus predicted ROC curves; and (iii) estimate the mag range between ROC curve pairs at  $\text{Pr}_D^{\max}$ .


# Radio Emissions from Explosions (1/2)

## *Predicted versus Observed ROC Curves for an SNR Detector*




# Radio Emissions from Explosions (2/2)

*How do we Quantify our Predictive Capability?*




# Defining Magnitude Discrepancy (1/2)

Magnitude difference between predicted and observed ROC curves, at constant probability (different ROC curves here, for illustration)




# Defining Magnitude Discrepancy (2/2)

Magnitude difference between predicted and observed ROC curves, at constant probability (different ROC curves here, for illustration)



# Radio Emissions from Explosions (1/2)


Hypothesis Test: Source 0: No Explosion; Source 1: An Explosion






# Radio Emissions from Explosions (2/2)


Hypothesis Test: Source 0: No Explosion; Source 1: An Explosion




# Magnitude Difference at Max Range Probability (1/5)




# Magnitude Difference at Max Range Probability (2/5)




# Magnitude Difference at Max Range Probability (3/5)



# Magnitude Difference at Max Range Probability (4/5)



# Magnitude Difference at Max Range Probability (5/5)




# *Quantifying the Predictive Capability of an Acoustic Emission, STA/LTA Detector*

*Estimate Magnitude Differences between  
Predicted and Observed ROC Curves*

*Process over 12 Days,  $-2.3 \leq \Delta m \leq 0$*


# Acoustic Emissions from Explosions

## Predicted versus Observed ROC Curves for an STA/LTA Detector






# Magnitude Difference at Max Range Probability (1/2)



# Magnitude Difference at Max Range Probability (2/2)




# *Quantifying the Predictive Capability of an Seismic Emission, Cross- Correlation Detector*

*Estimate Magnitude Differences between  
Predicted and Observed ROC Curves*


*Process over 12 Days,  $-2.3 \leq \Delta m \leq 0$*

# Acoustic Emissions from Explosions


## Predicted versus Observed ROC Curves for a Correlation Detector



# Magnitude Difference at Max Range Probability (1/2)



# Magnitude Difference at Max Range Probability (2/2)



# Monitoring Challenges

1. Does **mean** predicted detector performance match **mean** observed performance?
2. Does observed versus predicted detector performance exceed day-to-day observed variability? That is, does predicted performance assembled on day **A** match observations from day **A** better than observations assembled on day **B**?
3. What is the range in observed versus predicted magnitude discrepancies? That is, if a detector predictively identifies explosions of magnitude **m** with probability  $\text{Pr}_D$ , what is the observed, absolute range  $\Delta m$  the detector identifies explosions for probability  $\text{Pr}_D$ ?

# Some Solutions

1. SNR, radio detector is *effectively predictive*. STA/LTA acoustic detector is *qualitatively* predictive. Seismic correlation detector observations can *outperform predictions (explain!)*
2. Only SNR detector predictions consistently matched observations better than other observations.
3. Magnitude range **best/worst** cases, in probability range  $0.8 \leq \text{Pr}_D \leq 0.99$ 
  1. Radio:  $\Delta m = 0.025/0.33$
  2. Acoustic:  $\Delta m = 0.15/0.85$
  3. Seismic:  $\Delta m = 0.10/0.60$

# Summary

- **Objective:** build a multi-signature predictive capability. “Predictive” means that if a hypothetical explosion of an anticipated size/yield occurs, we must quantify how well we can detect, associate, screen, locate, or characterize that source.
- **Synthesis:** ROC curves are predictive when averaged over time. However, empirical ROC curves calculated at different times are often as predictive as calculated ROC curves, over 1-12 day periods

## Observed versus Theoretical Discrepancy Summary

Radio:  $\Delta m = 0.025/0.33$

Acoustic:  $\Delta m = 0.15/0.85$

Seismic:  $\Delta m = 0.10/0.60$